



Female plug-in connector - Rising clamp connection - Stackable version - Pitch 3,5mm - Poles 02÷24

GENERAL INFORMATION

pitch:	3,5 mm
housing height:	11,10 mm
housing depth:	15.5 mm
dimensional class:	medium
wire section:	2.5 mm ² / 14 AWG
clamp opening size:	1.8 x 2.6 mm
wire stripping:	max 8 mm
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS

current:	11A
voltage:	160V
impulse voltage:	2.5 kV

MECHANICAL CHARACTERISTICS

screw:	M2
max. torque:	0.25÷0.27 Nm / 2.3÷2.5 in.lbs

APPROVALS DATA



current:	-	EN 61984	UL 1059
	-	11A 2 and 3-pole	11A factory / 11A field
	-	9A 4÷24 poles	
voltage:	-	200V	300V
wire section:	-	2.5mm ²	14÷30AWG
torque:	-	0.25Nm	2.3Lb-in
FILE:	-	40048261	E178356

MATERIALS

housing:	PA - UL 94 V0
screw:	Galvanized steel
clamp/spring:	Nickel copper alloy
terminal:	Copper alloy

AVAILABLE COLOURS



other colours: upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
02	SH02-3,5	N/A	N/A	N/A
03	SH03-3,5	N/A	N/A	N/A
04	SH04-3,5	N/A	N/A	N/A
05	SH05-3,5	N/A	N/A	N/A
06	SH06-3,5	N/A	N/A	N/A
07	SH07-3,5	N/A	N/A	N/A
08	SH08-3,5	N/A	N/A	N/A
09	SH09-3,5	N/A	N/A	N/A
10	SH10-3,5	N/A	N/A	N/A
11	SH11-3,5	N/A	N/A	N/A
12	SH12-3,5	N/A	N/A	N/A
13	SH13-3,5	N/A	N/A	N/A
14	SH14-3,5	N/A	N/A	N/A
15	SH15-3,5	N/A	N/A	N/A
16	SH16-3,5	N/A	N/A	N/A
17	SH17-3,5	N/A	N/A	N/A
18	SH18-3,5	N/A	N/A	N/A
19	SH19-3,5	N/A	N/A	N/A
20	SH20-3,5	N/A	N/A	N/A
21	SH21-3,5	N/A	N/A	N/A
22	SH22-3,5	N/A	N/A	N/A
23	SH23-3,5	N/A	N/A	N/A
24	SH24-3,5	N/A	N/A	N/A