




MINIATURE FUSES
GLASS TUBE > 1.25 A WITH FILLING

M

Size **5 x 20 mm** Rated voltage **250 V** Standard **DIN 41571 Part 2**
medium time lag

Rated current	Part No.	Voltage drop mV	Pre-arcing I ² t _s -value A ² s	Rated breaking capacity	Power dissipation W	Weight (kg/100)	Pack
32 mA	172 000	640	0.0055	80 A	0.1	0.1	100
40 mA	172 000	630	0.008	80 A	0.1	0.1	100
50 mA	172 000	600	0.017	80 A	0.1	0.1	100
63 mA	172 000	560	0.025	80 A	0.1	0.1	100
80 mA	172 000	520	0.040	80 A	0.1	0.1	100
100 mA	172 000	470	0.055	80 A	0.1	0.1	100
125 mA	172 000	420	0.011	80 A	0.1	0.1	100
160 mA	172 000	370	0.036	80 A	0.1	0.1	100
200 mA	172 000	320	0.05	80 A	0.2	0.1	100
250 mA	172 000	280	0.1	80 A	0.2	0.1	100
315 mA	172 000	250	0.2	80 A	0.2	0.1	100
400 mA	172 000	230	0.4	80 A	0.2	0.1	100
500 mA	172 000	210	0.6	80 A	0.2	0.1	100
630 mA	172 000	190	0.9	80 A	0.2	0.1	100
800 mA	172 000	170	1.6	80 A	0.3	0.1	100
1 A	172 000	160	2.6	80 A	0.3	0.1	100
1.25 A	172 000	160	3.9	80 A	0.3	0.1	100
1.6 A	172 100	160	3.1	1000 A	0.8	0.12	100
2 A	172 100	160	5.2	1000 A	0.8	0.12	100
2.5 A	172 100	160	10	1000 A	0.9	0.12	100
3.15 A	172 100	160	20	1000 A	1.0	0.12	100
4 A	172 100	160	37	1000 A	1.1	0.12	100
5 A	172 100	150	72	1000 A	1.3	0.12	100
6.3 A	172 100	140	130	1000 A	1.6	0.12	100
8 A	172 100	140	230	300 A	2.0	0.12	100
10 A	172 100	120	370	300 A	2.5	0.12	100

¹ Consideration should be given to heat dissipation.



Pre-arcing time limits

Rated current	1.5 I _n	2.1 I _n	2.75 I _n	4 I _n	10 I _n
32 mA ↓ 1.25 A	> 1 h	< 10 min.	-	40 ms	5 ms
1.6 A ↓ 10 A		< 30 min.	-	2 s	90 ms

