

FUSE CLIPS & BLOCKS



保险丝夹及保险丝座






Suitable fuse: $\phi 6.35 \times 31.8\text{mm}$
 Maximum rated value: 10A.250V.AC
 Casing: Black thermoplastic
 Pole: Silver-plating brass

S1059




Suitable fuse: $\phi 5.2 \times 20\text{mm}$
 Maximum rated value: 6A.250V.AC
 Casing: White thermoplastic
 Pole: Nickel-plating brass

S1060

Suitable fuse: $\phi 6.35 \times 30\text{mm}$
 Maximum rated value: 10A.250V.AC
 Casing: Flame-retard plastic
 Pole: Silver-plating brass

S1061






Suitable fuse: $\phi 6.35 \times 31.8\text{mm}$
 Maximum rated value: 10A.250V.AC
 Casing: Black thermoplastic (bakelite)
 Pole: Silver-plating brass

S1062






Suitable fuse: $\phi 5.2 \times 20\text{mm}$
 Maximum rated value: 10A.250V.AC
 Holder: High temperature resisting
 Flame-retard plastic
 Pole: Silver-plating brass

S1068

Suitable fuse: $\phi 5.2 \times 20\text{mm}$
 Maximum rated value: 10A.250V.AC
 Holder: High temperature resisting
 Flame-retard plastic
 Pole: Silver-plating brass

S1069

S1075





S1076

TEMPERATURE LIMIT FUSE

限温保险丝



S1042-1



S1042-2




S1042-3