



Part No.	Colour	Wave Length	Lens Colour	Luminous Intensity(mcd)	Voltage(V)	Current(mA)	Deg
KTL050DDI	Red	700	Red Diffused	6-8	1.7-2.4	20	120°
KTL050CDI	Red	645		20-40	1.7-2.4	20	120°
KTL050ADI-S	Red	630		100-200	1.7-2.4	20	120°
KTL050ADI-U	Red	640		200-400	1.7-2.4	20	120°
KTL050ADI-t	Red	623		600-1200	1.7-2.4	20	120°
KTL050KDI	Green	572	Green Diffused	6-8	1.7-2.4	20	120°
KTL050JDI	Green	572		40-60	1.7-2.4	20	120°
KTL050JDI-S	Green	572		100-200	1.7-2.4	20	120°
KTL050JDI-U	Green	572		200-400	1.7-2.4	20	120°
KTL050IDI	Yellow	590	Yellow Diffused	100-200	1.8-2.1	20	120°
KTL050IDI-S	Yellow	590		150-300	1.8-2.1	20	120°
KTL050IDI-U	Yellow	590		400-800	1.8-2.1	20	120°
KTL050IDI-T	Yellow	590		600-1000	1.8-2.1	20	120°
KTL050FDI	Orange	610	Orange Diffused	60-80	1.8-2.1	20	120°
KTL050FDI-S	Orange	610		250-450	1.8-2.1	20	120°
KTL050FDI-U	Orange	610		450-650	1.8-2.1	20	120°
KTL050BGDI	Blue-Green	510	Green Diffused	2000-3000	3.0-3.6	20	120°
KTL050BGDI-U	Blue-Green	510		3000-4000	3.0-3.6	20	120°
KTL050BLDI	Blue	470	Blue Diffused	300-400	3.0-3.6	20	120°
KTL050BHDI	Blue	470		400-800	3.0-3.6	20	120°
KTL050BUDI	Blue	470		800-1200	3.0-3.6	20	120°
KTL050PGDI	Pure Green	525	Green Diffused	2000-3000	3.0-3.6	20	120°
KTL050PGDI-S	Pure Green	525		3000-4000	3.0-3.6	20	120°
KTL050PGDI-U	Pure Green	525		4000-5000	3.0-3.6	20	120°
KTL050WDI	White	----	White Diffused	800-1500	3.0-3.6	20	120°
KTL050WHDI	White	----		1500-2000	3.0-3.6	20	120°
KTL050WUDI	White	----		2000-2500	3.0-3.6	20	120°