



Part No.	Colour	Wave Length	Lens Colour	Luminous Intensity(mcd)	Voltage(V)	Current(mA)	Deg
KTL050DCI	Red	700	Water Clear	10-20	1.7-2.4	20	25°
KTL050CCI	Red	645		80-200	1.7-2.4	20	25°
KTL050ACI-S	Red	630		1000-2000	1.7-2.4	20	25°
KTL050ACI-U	Red	640		2000-4000	1.7-2.4	20	25°
KTL050ACI-T	Red	623		3500-5500	1.7-2.4	20	25°
KTL050KCI	Green	572	Water Clear	6-10	1.7-2.4	20	25°
KTL050JCI	Green	572		100-200	1.7-2.4	20	25°
KTL050JCI-S	Green	572		1000-2000	1.7-2.4	20	25°
KTL050JCI-U	Green	572		2000-3000	1.7-2.4	20	25°
KTL050ICI	Yellow	590	Water Clear	1000-2000	1.7-2.4	20	25°
KTL050ICI-S	Yellow	590		1500-3000	1.7-2.4	20	25°
KTL050ICI-U	Yellow	590		3000-5000	1.7-2.4	20	25°
KTL050ICI-T	Yellow	590		5000-7000	1.7-2.4	20	25°
KTL050FCI	Orange	610	Water Clear	600-800	1.7-2.4	20	25°
KTL050FCI-S	Orange	610		2500-4500	1.7-2.4	20	25°
KTL050FCI-U	Orange	610		4500-6500	1.7-2.4	20	25°
KTL050BGCI	Blue-Green	510	Water Clear	11000-13000	3.0-3.6	20	25°
KTL050BGCI-U	Blue-Green	510		13000-16000	3.0-3.6	20	25°
KTL050BLCI	Blue	470	Water Clear	3000-4000	3.0-3.6	20	25°
KTL050BHCI	Blue	470		4000-5000	3.0-3.6	20	25°
KTL050BUCI	Blue	470		5000-6000	3.0-3.6	20	25°
KTL050PGCI	Pure Green	525	Water Clear	12000-14000	3.0-3.6	20	25°
KTL050PGCI-S	Pure Green	525		14000-16000	3.0-3.6	20	25°
KTL050PGCI-U	Pure Green	525		16000-18000	3.0-3.6	20	25°
KTL050WCI	White	-----	Water Clear	7000-8000	3.0-3.6	20	25°
KTL050WHCI	White	-----		8000-9000	3.0-3.6	20	25°
KTL050WUCI	White	-----		9000-11000	3.0-3.6	20	25°